

Technical data




Electronics housing

Series B.tronic

Type description **BT-142608**

Article number **1540000000**



BT-142608

Standard version

Scope of delivery:

Gehäuseunterteil /
Lower part of enclosure /
Partie inférieure du boîtier
Gehäusedeckel inklusive Kunststoff-Schraubkanalabdeckkappen/
Enclosure cover, including plastic screw channel cover caps /
Couvercle de boîtier, avec capuchons en plastique pour les canaux de vissage
Deckelschrauben (Torx TX25) lose beigelegt /
Cover screws (Torx TX25) included separately /
Vis du couvercle (Torx TX25) fournies séparément
Erdungsschraube im Unterteil und Deckel /
Grounding screw in the base and lid /
Vis de mise à la terre dans la partie inférieure et le couvercle
RAL7037 (staubgrau) /
RAL7037 (dusty grey) /
RAL7037 (gris poussière)
Deckeldichtung PUR /
lid gasket PUR /
Joint de couvercle en PUR
Einzelverpackung in Folie /
Single packaging in foil /
Emballage individuel sous film

Maximum possible number of threads (data for same diameter, not mixed!)

ISO M	M12	M16	M20	M25	M32	M40	M50	M63
Side A/B	14	6	5	4	3	0	0	0
Side C/D	4	2	1	1	1	0	0	0

BERNSTEIN AG . Hans-Bernstein-Straße 1 . 32457 Porta Westfalica . www.bernstein.eu

Technical changes and errors excepted.

This data sheet corresponds to the technical status as of 18.09.2026 [TT.MM.JJJJ] and will not be withdrawn in the event of changes.

Technical data



Electronics housing

Series B.tronic

Properties table BT-142608			Article number
			1540000000
Specification	Value	according to standard	Comment
General data			
Weight	1854g		
External dimensions	260x140x83		
Degree of protection			
IP code	—	DIN EN 60529	
IP code	—	DIN EN 60529	
IK code	—	DIN EN 62262	
Materials			
Enclosure	EN AC-ALSi12 (Fe) EN AC-44300	DIN EN 1706:05/98	Aluminium die casting Alloy 230
Lid fastener	A2-70	DIN EN ISO 3506-1	Lid screws
Additional screws	—	—	—
Spring washer	—	—	—
Cover caps	Polyamid (PA6)	—	Colour: similar to RAL 9005 (deep black)
Seal	PUR	—	Colour: black-grey 2K-polyurethane foam gasket
Toxic behaviour	Halogenfrei / Halogen-free / Sans halogène	—	—
Mechanical properties			
Torques			
Cover fastener	2,0 Nm		—
Ground screw	2,0 Nm 2,0 Nm		Base Lid
Fastening accessories	2,0 Nm		e.g. support rail, mounting plate
Other fastening	2,0 Nm		Screw channel
Maximum installation weight	2,7 Kg		—
Thermal properties			
Temperature range			
Enclosure complete	-40°C bis +90°C	—	Housing standard powder coated
Enclosure material	—	—	—
Seal	-40°C bis +100°C	—	PUR
Fire behaviour			
Flammability	—	—	—
Glow wire test	—	—	—
Temperature index Enclosure material			
RTI (tensile strength)	—	—	—
RTI (impact strength)	—	—	—
RTI (dielectric strength)	—	—	—
Heat resistance			
Insulation class	—	—	—
Fire behaviour - Fire protection in railway vehicles according to EN 45545-2:2020-10			
Requirement set R1	—	—	—
Requirement set R6	—	—	—
Requirement set R7	—	—	—
Oxygen index	—	—	—
Storage temperature	-20°C bis +60°C	—	—
Thermal resistance	2,21 K/W	—	taking into account the effective power loss

BERNSTEIN AG . Hans-Bernstein-Straße 1 . 32457 Porta Westfalica . www.bernstein.eu

Technical changes and errors excepted.

This data sheet corresponds to the technical status as of 18.09.2026 [TT.MM.JJJJ] and will not be withdrawn in the event of changes.

Technical data



Electronics housing

Series B.tronic

Properties table BT-142608

Article number 1540000000

Specification	Value	according to standard	Comment
Usual operating conditions according to DIN EN 62208			
Ambient temperature			
<i>Indoor installation</i>	-5°C bis +40°C	—	on average over 24h +35°C
<i>Outdoor installation</i>	-25°C bis +40°C	—	on average over 24h +35°C
Relative humidity			
<i>Indoor installation</i>	max. 50% bei +40°C	—	at low temperatures also higher (e.g. 90% at 20°C); occasionally condensation permissible
<i>Outdoor installation</i>	zeitweise / temporary / temporairement 100 % bei +25°C	—	at low temperatures also higher (e.g. 90% at 20°C); occasionally condensation permissible
Chemical properties			
Corrosion resistance	—	DIN EN 62208/9.13.2.1	IEC 60068-2-30 and IEC 60068-2-11
Corrosion resistance	—	DIN EN 62208/9.13.2.2	IEC 60068-2-30 and IEC 60068-2-11
Salt spray test	—	—	—
Resistance list for enclosure materials and seals			see catalogue details
Electrical properties			
Protection class	I	EN 61140 / VDE 0140-1	 Protection by protective conductor
Rated voltage	max. 1000V (AC) max. 1500V (DC)	—	—
Surface resistance	—	IEC 60093	—
Dielectric strength	—	IEC 60243-1	—
Further specifications			
General tolerances			
<i>Casting tolerance</i>	DCTG 7 - GCTG 3	DIN EN ISO 8062-3	Casting tolerance
<i>Machining tolerance</i>	mH	DIN ISO 2768	Machining tolerance
<i>Country of Melt</i>	China		
<i>Country of Pour</i>	China		
<i>Completion of the end product</i>	Germany (Deutschland)		
Product standard	—	DIN EN 62208	Empty enclosures for low-voltage switchgear and controlgear assemblies
Approval			
<i>c UL us</i>	—	UL 508A / C22.2	—
<i>ATEX / IECeX</i>	 —	—	—
<i>DNV</i>	—	—	—
Conformities / Directives			
<i>Directive 2011/65/EU (RoHs)</i>	konform/compliant/conforme	2011/65/EU (RoHs)	RoHs
<i>Low Voltage Directive</i>	—	2014/35/EU	—
<i>Electrical Equipment (safety) Regulations 2016 (CA UK)</i>	—	2016 NO.1101	—

BERNSTEIN AG . Hans-Bernstein-Straße 1 . 32457 Porta Westfalica . www.bernstein.eu

Technical changes and errors excepted.

This data sheet corresponds to the technical status as of 18.09.2026 [TT.MM.JJJJ] and will not be withdrawn in the event of changes.