



Inductive Proximity Switch Series M12

Description **KIN-M12NS/004-KL2V**

Article number **6532304001**

Wiring Diagram




Identifying characteristics in accordance with EN 60947-5-2

Electrical data	
Rated operating distance	S_n 4 mm
Standard target	12 mm x 12 mm, t = 1 mm, material: FE360
Real sensing distance	S_r 3,6 ... 4,4 mm
Assured operating distance	S_a 0 ... 3,2 mm
Switching element function	DC, N.O.
Repeat accuracy	R \leq 5 %
Differential travel (hysteresis)	H \approx 8 %
Rated operational voltage	U_e 12 - 24 V DC
Operational voltage range	U_B 10 - 30 V DC
Rated insulation voltage	U_i 75 V DC
Rated impulse withstand voltage	U_{imp} 500 V
Voltage drop	U_d \leq 2 V specification
Utilization category	DC 13
Rated operational current	I_e 200 mA \pm 10 %
Minimum operating current	I_m 1 mA
Off-state current	I_r $<$ 0,1 mA
No-load supply current	I_o $<$ 10 mA
Switching element	permanent overload and s.c.p.
Short-circuit protection	pulsed, current-limited and thermal
Frequency of operating cycles	f 1000 Hz
Mounting	non flush
False polarity protection	yes
Time delay before availability	t_v $<$ 300 ms

Mechanical Data	
Front cap	LCP, black
Enclosure	brass, nickel plated
End cap	PA12, transparent
Temperature range	- 20 °C ... + 70 °C (cable not fixed mounted) - 25 °C ... + 70 °C (cable fixed mounted)
Type of protection	IP67 / NEMA Type 1
Function indication	LED, yellow
Degree of pollution	3 (Pollution of the sensing surface may decrease operating distance)
Termination type	Cable 3 x 0,14 mm ² x 2 m ±5 %, PUR - Outer jacket, black
For attachment	2 x hexagon nut (tightening torque ≤ 10 Nm) and 2 x toothed washer

Product reliability (in acc. with DIN EN 61709 (SN 29500))	
MTTF (at 40 °C)	>1150 years

EU Conformity	
acc. to directive 2014/30/EU (EMC-Directive)	

Approvals	
	

Notes	
To be used with a class 2 power supply according to UL approval.	
Further data and information can be found at www.bernstein.eu .	