

Float switch


Series Standard-Float switch

Description **MAM-713 LT05 0249**



Article number **6816200009**

Wiring diagram

(non-actuated state)



Performance diagram








Electrical data

Rated voltage	U_r	250 V
max. switching current		1,0 A
max. switching capacity		60 VA
min. switching capacity		3 VA
Rated insulation voltage	U_i	300 V AC
Rated impulse withstand voltage	U_{imp}	4 kV AC
Overvoltage category		II
Switching element		1 x C.O., falling level
Protection class		II (totally insulated)

Mechanical data	
Flange material	PA6.6
Switching tube material	CuZn37 (CW508L)
Float material	POM
- density	about 0,7 g/cm ³ ±10 %
- depth of immersion	18 mm ± 2 mm (to a fluid-density of 1 g/cm ³)
Grip screw material	CuSn8 (CW453K)
Gasket material	NBR
Ambient air temperature	-5 °C to +60 °C
Liquid temperature	-5 °C to +60 °C
Connection	Connector acc. to DIN EN 175 301-803
Protection type	IP 65 acc to IEC529 / EN 60529 (only in fully locked position with it's plugs)
Max. pressure	5 bar

Standards
DIN EN 60947-5-1

EU Conformity
acc. to directive 2014/35/EU (Low-Voltage-Directive)

Inductive loads	
Direct current  Suppression of voltage peaks with a free-wheeling diode	Alternating voltage  Suppression of voltage peaks with a VDR
 Suppression of voltage peaks with an RC element	 Suppression of voltage peaks with an RC element
Capacitive loads and lamp loads	
 Contact protection with resistors for limiting current	